

RUSH+

100% CUSTOMISABLE

The RUSH + adopts an ultra-sporty design with its co-injected and ultra-flexible temples ... and is 100% customisable.

 PLATINUM



RUSHPPSI



RUSHPPSF



RUSHPTWI



KITRUSHFS
Kit foam & strap




Bi-colour & bi-material temples
-Black / Grey (Twilight version)
-Black / Red (clear & smoke versions)

Also available in
- Blue / Black
- Green / Black
- Yellow / Black
- Orange / Black
(from 300 pieces)



Non-slip bridge



Foam & strap
version (optional)



26 g

Fully customise the RUSH +:
lens marking, temples colour ...

Informations & conditions : marketing@bolle-safety.com

- + UPPER PROTECTION
- +  PLATINUM COATING (P)
- + CO-INJECTED, ULTRA-FLEX TEMPLES
- + NON-SLIP BRIDGE
- + BI-COLOUR TEMPLES DEPENDING ON VERSION

bolle
SAFETY

RUSH+

100% CUSTOMISABLE

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
RUSH+	Clear	RUSHPPSI	2C-1,2 1 FT KN C€	EN166 FT C€	Anti-scratch/Anti-fog
	Smoke	RUSHPPSF	5-3,1 1 FT KN C€	EN166 FT C€	Anti-scratch/Anti-fog
	Twilight	RUSHPTWI	5-2 1 FT KN C€	EN166 FT C€	Anti-scratch/Anti-fog
	Kit foam & strap	RUSHKITFS	-	-	

LENS MARKING

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

K. Resistance to surface damage by fine particles

N. Resistance to fogging

C€ European standard Manufacturer name

TECHNOLOGY

B-TWILIGHT

The new B-Twilight technology offers the advantages of ESP with a double anti-fog coating (on both sides of the lenses) to prevent fogging in the most challenging conditions.

Designed and used in low light conditions, it improves contrast. Its light transmission rate is perfect for outdoors, particularly early morning and late evening. B-Twilight filters 76% of blue light.

PLATINUM

This permanent coating on both sides of the lens gives them a high resistance to scratching (1.4 cd / m²), to the most aggressive chemicals and delays the onset of fogging for 2 minutes. In all circumstances and at all times the PLATINUM lens innovation guarantees your eyes improved protection.

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

C€ European standard Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly with a mild soap detergent or optical solution.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: Store between 5 and 40 °, humidity <90%.

PACKAGING AND EAN13 CODE

	RUSHPPSI	RUSHPPSF	RUSHTWI	KITRUSHFS
Individual plastic bag	3660740007041	3660740007058	3660740007065	3660740006488
10 safety spectacles per inner box	3660740107048	3660740107055	3660740107062	3660740106485
240 safety spectacles per outer pack	3660740207045	3660740207052	3660740207069	3660740206482

CHARACTERISTICS

LENSES	PC - 2,2 mm - Curve 9
FRAME	PC
TEMPLES	PC + TPR
STRAP	TBC
FOAM	SBR
SPARE LENSES	No



Non-contractual pictures

23/10/2013

Europe Bollé Safety
95 rue Louis Guérin
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

bolle
SAFETY