

FEATURES

- Abrasion and tear resistant, with a secure grip
- Comfortable with anatomical shaped fit, allowing excellent freedom of movement and reduction of hand fatigue
- Recommended for precise operations requiring maximum dexterity
- Ideal for detailed assembly, light fabrication and small parts handling

DESCRIPTION

- Seamless nylon liner with a Polyurethane coated palm
- Elasticated wrist provides a secure, comfortable fit
- Breathable back of hand designed to reduce perspiration and skin irritation
- Lint free, reducing the risk of product contamination
- Black colouring to hide soiling



TECHNICAL DATA

AVAILABLE SIZES 6/XS • 7/S • 8/M • 9/L • 10/XL • 11/XXL

PACKAGING 10/120
Pairs per pack/box

COLOUR OF LINER/COATING Black/Black

TYPICAL APPLICATIONS

- Manufacturing
- Construction
- Assembly
- Automotive
- General Maintenance
- Ceiling Fixing

Cat
CE II



EN 388 standard

Abrasion	4
Cut	1
Tear	3
Puncture	1

EN388: 2003



Recommendations For Use

- Not for use with liquids. Do not use near moving machines if there is a risk of entanglement.
- Storage: Gloves should be ideally stored in cool, dry conditions in original packaging and away from direct sunlight.
- Cleaning/Maintenance: Both new and used gloves should be thoroughly inspected before being worn to ensure no damage is present. Gloves should not be left in contaminated condition if reuse is intended in which case gloves should be cleaned as far as possible. If appropriate, decontamination may take place under lukewarm water using laundry soap and detergent. Don't use chlorine bleaches.