Pharmacy Essential Refrigerator

47L Pharmacy Essential Countertop Fridge with Solid Door

Product code PESR47DC-UK

SKU code 444411286










Key features

- √ Temperature range of +2°C to +8°C
- √ Air temperature probe





Temperatures are easy to read on the clear digital display. Read, record, and reset simply with the touch of a button.



Fitted Lock

Integrated lock, comes with two keys for added security and access control, to keep contents safe.

- ✓ Audible and visual temperature alarms
- √ Solid and glass door options



Flexible Storage

Multiple shelf positions provide a flexible storage options for all your needs.



Anti-Microbial Handle

Our handles have an anti-microbial powder coating which inhibits the growth of microbes to help prevent cross contamination.



SKU Code	444411286
Product Code	PESR47DC-UK
Gross Capacity (litres)	47L
Net Capacity (litres)	35L
Unit External Width (mm)	475mm
Unit External Depth (mm)	445mm
Unit External Height (mm)	565mm
Product Weight (kg)	18.32kg
Packed Width (mm)	505mm
Packed Depth (mm)	510mm
Packed Height (mm)	585mm
Packed Weight (kg)	20.4kg
Country of Origin	UK
Internal Dimensions (mm) (WxDxH)	405mm x 355mm x 425mm
Temperature Range	+2°C to +8°C
Colour	White/Green
External Finish	Painted Steel
Internal Finish	HIPS*
Type of plastic	SRL800 (HIPS/ABS mix)
Door Finish	Painted Steel / HIPS*
Door Type	Solid
Door Style	Hinged, Reversible
Door Liner	- Flat
Door Open Depth (mm)	905mm
Replacement Door Seal	Yes
Open Door Sensor	Yes
Lock	Yes, 2 Keys
Adjustable Feet (number & position)	2 Adjustable (front)
Porthole	Yes
Porthole Size	16mm
Porthole Location	Rear Bottom (Right)
Temperature Display on Panel	Yes
Temperature Alarm	Yes
Audible Alarms	Yes
Visual Alarms	Yes
Number of Shelves/Drawers	1
Number of Shelf Positions	3
Shelf Size (mm) (WxDxH)	418mm x 200mm x 6mm
Shelf Material	White Polythene Coated Wire
Drawer Size (mm) (WxDxH)	2@ 408mm x 405mm x 195mm
Number of Baskets	1
Basket Material	White Polythene Coated Wire
Basket Size (mm) (WxDxH)	396mm x 165mm x 150mm
Interior Light	No
Fan	
	Yes - Axial
Spark Free	Yes - Axial No
Spark Free Defrost setting	
Spark Free Defrost setting Controller Type	No
Spark Free Defrost setting Controller Type Number of Probes	No Auto (Off Cycle) Digital, External
Spark Free Defrost setting Controller Type Number of Probes Probe Type	No Auto (Off Cycle) Digital, External 1 Air
Spark Free Defrost setting Controller Type Number of Probes Probe Type Ambient Temperature Range	No Auto (Off Cycle) Digital, External 1 Air 10°C to 32°C
Spark Free Defrost setting Controller Type Number of Probes Probe Type Ambient Temperature Range Refrigerant Type	No Auto (Off Cycle) Digital, External 1 Air 10°C to 32°C R600a/25g
Spark Free Defrost setting Controller Type Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug	No Auto (Off Cycle) Digital, External 1 Air 10°C to 32°C R600a/25g Yes
Spark Free Defrost setting Controller Type Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available	No Auto (Off Cycle) Digital, External 1 Air 10°C to 32°C R600a/25g Yes No
Spark Free Defrost setting Controller Type Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply	No Auto (Off Cycle) Digital, External 1 Air 10°C to 32°C R600a/25g Yes No 220-240V
Spark Free Defrost setting Controller Type Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz)	No Auto (Off Cycle) Digital, External 1 Air 10°C to 32°C R600a/25g Yes No 220-240V 50/60Hz
Spark Free Defrost setting Controller Type Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Power (W)	No Auto (Off Cycle) Digital, External 1 Air 10°C to 32°C R600a/25g Yes No 220-240V 50/60Hz 70W
Spark Free Defrost setting Controller Type Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Power (W) Max Current Rating (A)	No Auto (Off Cycle) Digital, External 1 Air 10°C to 32°C R600a/25g Yes No 220-240V 50/60Hz 70W 0.6A
Spark Free Defrost setting Controller Type Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Power (W) Max Current Rating (A) Energy Consumption (kWh/24h)	No Auto (Off Cycle) Digital, External 1 Air 10°C to 32°C R600a/25g Yes No 220-240V 50/60Hz 70W 0.6A 0.54kWh/24h
Spark Free Defrost setting Controller Type Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Power (W) Max Current Rating (A) Energy Consumption (kWh/24h) Energy Consumption AE (kWh)	No Auto (Off Cycle) Digital, External 1 Air 10°C to 32°C R600a/25g Yes No 220-240V 50/60Hz 70W 0.6A 0.54kWh/24h 197.1kWh
Spark Free Defrost setting Controller Type Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Power (W) Max Current Rating (A) Energy Consumption (kWh/24h) Energy Consumption AE (kWh) Noise Level (dB)	No Auto (Off Cycle) Digital, External 1 Air 10°C to 32°C R600a/25g Yes No 220-240V 50/60Hz 70W 0.6A 0.54kWh/24h 197.1kWh 46.7dB
Spark Free Defrost setting Controller Type Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Power (W) Max Current Rating (A) Energy Consumption (kWh/24h) Energy Consumption AE (kWh) Noise Level (dB) Insulation Thickness (mm)	No Auto (Off Cycle) Digital, External 1 Air 10°C to 32°C R600a/25g Yes No 220-240V 50/60Hz 70W 0.6A 0.54kWh/24h 197.1kWh 46.7dB 35mm
Spark Free Defrost setting Controller Type Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Power (W) Max Current Rating (A) Energy Consumption (kWh/24h) Energy Consumption AE (kWh) Noise Level (dB) Insulation Thickness (mm) Insulation Type	No Auto (Off Cycle) Digital, External 1 Air 10°C to 32°C R600a/25g Yes No 220-240V 50/60Hz 70W 0.6A 0.54kWh/24h 197.1kWh 46.7dB 35mm High Density Polyurothane Foam
Spark Free Defrost setting Controller Type Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Power (W) Max Current Rating (A) Energy Consumption (kWh/24h) Energy Consumption AE (kWh) Noise Level (dB) Insulation Thickness (mm)	No Auto (Off Cycle) Digital, External 1 Air 10°C to 32°C R600a/25g Yes No 220-240V 50/60Hz 70W 0.6A 0.54kWh/24h 197.1kWh 46.7dB 35mm

