







The touch screen controller is completely flat so can be thoroughly cleaned and disinfected as there are no raised buttons to collect dirt and germs. The controller displays, alarms and records minimum and maximum temperatures for both temperature probes. Like a mobile phone touch screen it locks after 30 seconds to ensure that buttons can't be activated accidently.

For extra security, there is a digital lock version RLDF0219DIGLOCK which solves the problem of generic keys, but whatever the preferred model, for a small additional cost we can provide a manufacturers' calibration certificate from our in house UKAS temperature calibration laboratory No:8898.

We are confident that this pharmacy refrigerator will provide you with many years of fault free service. However, for extra peace of mind your RLDF0219 comes complete with a FREE UK 5 year parts and labour warranty.





While you're registering your warranty, why not purchase a micro SD card and adapter for transferring data recorded by the controller from the fridge to your computer at half price?

The IntelliCold[®] controller records alarm states, fridge operation, door openings and temperature data for both probes at minute intervals. You can only view and store this data on a computer by purchasing a specially encoded micro SD card from Labcold. This data helps you with record keeping and regulatory inspections, plus if you have an issue, you can establish the exact duration and severity of the event.

RLDF0219 Pharmacy & Vaccine Refrigerator

Part Number	RLDF0219
Capacity (Litres)	66
Style	Bench Top
Exterior Dimensions (HxWxD)	735 x 450 x 510mm
Interior Dimensions (HxWxD)	588 x 331 x 226mm
Temperature Range	+2°C to +8°C
Operating Temperature	+5°C
Power Consumption Kwh/24hrs	1.3
Interior Construction	Moulded Plastic
Exterior Construction	Powder Coated Steel
Shelves	3
Brackets for Wall Mounting	\checkmark
Net Weight (kg)	34
Door Style	Solid
Door Hinging	Right (can be reversed at time of manufacture)
Self Closing Door	\checkmark
Key Lock	\checkmark
Digital Temperature Control	\checkmark
Digital Temperature Display	\checkmark
Internal Light	\checkmark
High/Low Temperature Alarm	\checkmark
Minimum/Maximum Temperature Recording	\checkmark
Automatic Temperature & Fridge Operation Data Recording	\checkmark
Door Open Alarm	\checkmark
Mains Failure Alarm	\checkmark
Alarm Battery Back-Up	\checkmark
Second Temperature Probe	\checkmark
Off Cycle Auto Defrost	\checkmark
Fan Assisted Cooling	\checkmark
Remote Alarm Contacts	\checkmark
Access Port	\checkmark
DH Green Book Guidelines Compliant	✓



01256 705 570









The touch screen controller is completely flat so can be thoroughly cleaned and disinfected as there are no raised buttons to collect dirt and germs. The controller displays, alarms and records minimum and maximum temperatures for both temperature probes. Like a mobile phone touch screen it locks after 30 seconds to ensure that buttons can't be activated accidently.

For extra security, there is a digital lock version RLDF0519DIGLOCK which solves the problem of generic keys, but whatever the preferred model, for a small additional cost we can provide a manufacturers' calibration certificate from our in house UKAS temperature calibration laboratory No:8898.

We are confident that this pharmacy refrigerator will provide you with many years of fault free service. However, for extra peace of mind your RLDF0519 comes complete with a FREE UK 5 year parts and labour warranty.



While you're registering your warranty, why not purchase a micro SD card and adapter for transferring data recorded by the controller from the fridge to your computer at half price?

> The IntelliCold[®] controller records alarm states, fridge operation, door openings and temperature data for both probes at minute intervals. You can only view and store this data on a computer by purchasing a specially encoded micro SD card from Labcold. This data helps you with record keeping and regulatory inspections, plus if you have an issue, you can establish the exact duration and severity of the event.

RLDF0519 Pharmacy & Vaccine Refrigerator

Capacity (Litres)150StyleUnder CounterExterior Dimensions (HxWxD)835 x 600 x 600mm (HxWxD)Interior Dimensions (HxWxD)690 x 480 x 410mmTemperature Range+2°C to +8°COperating Temperature+5°CPower Consumption Kwh/24hrs1.41Interior ConstructionPowder Coated SteelExterior ConstructionPowder Coated SteelShelves3Net Weight (kg)51Internal Drawers Available·Door StyleSolidDoor HingingRight (can be reversed at time of manufacture)Self Closing Door·Key Lock·Digital Temperature Control·Joigtal Temperature Display·Minimum/Maximum Temperature Recording·Automatic Temperature Alarm·Door Open Alarm·Mains Failure Alarm·Alarm Battery Back-Up·Off Cycle Auto Defrost·Fan Assisted Cooling·	Part Number	RLDF0519
Exterior Dimensions (HXWxD)835 x 600 x 600mmInterior Dimensions (HXWxD)690 x 480 x 410mmTemperature Range+2°C to +8°COperating Temperature+5°CPower Consumption Kwh/24hrs1.41Interior ConstructionPowder Coated SteelExterior ConstructionPowder Coated SteelShelves3Net Weight (kg)51Internal Drawers Available✓Door StyleSolidDoor HingingSelf Closing Door✓Key Lock✓Digital Temperature Othorp✓Minimum/Maximum Temperature Recording✓Minimum/Maximum Temperature Recording✓AutomaticTemperature Alarm✓Mains Failure Alarm✓Alarm Battery Back-Up✓Off Cycle Auto Defrost✓	Capacity (Litres)	150
Interior Dimensions (HxWxD)835 x 600 x 600mmInterior Dimensions (HxWxD)690 x 480 x 410mmTemperature Range+2°C to +8°COperating Temperature+5°CPower Consumption Kwh/24hrs1.41Interior ConstructionPowder Coated SteelExterior ConstructionPowder Coated SteelShelves3Net Weight (kg)51Internal Drawers Available✓Door StyleSolidDoor HingingRight (can be reversed at time of manufacture)Self Closing Door✓Key Lock✓Digital Temperature Control✓Joigtal Temperature Display✓Hinhimum/Maximum Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Door Open Alarm✓Alarm Battery Back-Up✓Off Cycle Auto Defrost✓	Style	Under Counter
Harmonic (HxWxD)690 x 480 x 410mmTemperature Range+2°C to +8°COperating Temperature+5°CPower Consumption Kwh/24hrs1.41Interior ConstructionPowder Coated SteelExterior ConstructionPowder Coated SteelShelves3Net Weight (kg)51Internal Drawers Available·Door StyleSolidDoor HingingRight (can be reversed at time of manufacture)Self Closing Door·Key Lock·Digital Temperature Control·Joigtal Temperature Display·Internal Light·High/Low Temperature Alarm·Minimum/Maximum Temperature Recording·Door Open Alarm·Mains Failure Alarm·Alarm Battery Back-Up·Off Cycle Auto Defrost·		835 x 600 x 600mm
Operating Temperature+5°CPower Consumption Kwh/24hrs1.41Interior ConstructionPowder Coated SteelExterior ConstructionPowder Coated SteelShelves3Net Weight (kg)51Internal Drawers Available✓Door StyleSolidDoor HingingRight (can be reversed at time of manufacture)Self Closing Door✓Key Lock✓Digital Temperature Control✓Jinternal Light✓High/Low Temperature Alarm✓Minimum/Maximum Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Door Open Alarm✓Alarm Battery Back-Up✓Off Cycle Auto Defrost✓		690 x 480 x 410mm
Power Consumption Kwh/24hrs1.41Interior ConstructionPowder Coated SteelExterior ConstructionPowder Coated SteelShelves3Net Weight (kg)51Internal Drawers AvailableJoor StyleSolidDoor HingingRight (can be reversed at time of manufacture)Self Closing DoorKey LockDigital Temperature ControlJinternal LightHigh/Low Temperature AlarmMinimum/Maximum Temperature RecordingAutomatic Temperature & Fridge Operation Data RecordingJoor Open AlarmAlarm Battery Back-UpOff Cycle Auto DefrostOff Cycle Auto Defrost	Temperature Range	+2°C to +8°C
Kwh/24hrs1.41Interior ConstructionPowder Coated SteelExterior ConstructionPowder Coated SteelShelves3Net Weight (kg)51Internal Drawers Available✓Door StyleSolidDoor HingingRight (can be reversed at time of manufacture)Self Closing Door✓Key Lock✓Digital Temperature Control✓Jinternal Light✓High/Low Temperature Alarm✓Minimum/Maximum Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Mains Failure Alarm✓Alarm Battery Back-Up✓Off Cycle Auto Defrost✓	Operating Temperature	+5°C
Exterior ConstructionPowder Coated SteelShelves3Net Weight (kg)51Internal Drawers Available✓Door StyleSolidDoor HingingRight (can be reversed at time of manufacture)Self Closing Door✓Key Lock✓Digital Temperature Control✓Internal Light✓High/Low Temperature Alarm✓Minimum/Maximum Temperature Recording✓Door Open Alarm✓Mains Failure Alarm✓Alarm Battery Back-Up✓Second Temperature Probe✓Off Cycle Auto Defrost✓		1.41
Shelves3Net Weight (kg)51Internal Drawers Available✓Door StyleSolidDoor HingingRight (can be reversed at time of manufacture)Self Closing Door✓Key Lock✓Digital Temperature Control✓Digital Temperature Display✓High/Low Temperature Alarm✓Minimum/Maximum Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Door Open Alarm✓Alarm Battery Back-Up✓Off Cycle Auto Defrost✓	Interior Construction	Powder Coated Steel
Net Weight (kg)51Internal Drawers Available✓Door StyleSolidDoor HingingRight (can be reversed at time of manufacture)Self Closing Door✓Key Lock✓Digital Temperature Control✓Digital Temperature Display✓Internal Light✓High/Low Temperature Alarm✓Minimum/Maximum Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Door Open Alarm✓Alarm Battery Back-Up✓Off Cycle Auto Defrost✓	Exterior Construction	Powder Coated Steel
Internal Drawers AvailableInternal Drawers AvailableDoor StyleSolidBoor HingingRight (can be reversed at time of manufacture)Self Closing Door✓Key Lock✓Digital Temperature Control✓Digital Temperature Display✓High/Low Temperature Alarm✓Minimum/Maximum Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Door Open Alarm✓Alarm Battery Back-Up✓Off Cycle Auto Defrost✓	Shelves	3
Door StyleSolidDoor HingingRight (can be reversed at time of manufacture)Self Closing Door✓Key Lock✓Migital Temperature Control✓Jigital Temperature Display✓Internal Light✓High/Low Temperature Alarm✓Minimum/Maximum Temperature Recording✓Joor Open Alarm✓Mains Failure Alarm✓Alarm Battery Back-Up✓Off Cycle Auto Defrost✓	Net Weight (kg)	51
Door HingingRight (can be reversed at time of manufacture)Self Closing DoorSelf Closing DoorKey LockDigital Temperature ControlJoigital Temperature DisplayInternal LightHigh/Low Temperature AlarmMinimum/Maximum Temperature RecordingJoor Open AlarmMains Failure AlarmAlarm Battery Back-UpSecond Temperature ProbeOff Cycle Auto Defrost	Internal Drawers Available	\checkmark
Door Hingingreversed at time of manufacture)Self Closing DoorKey LockDigital Temperature ControlDigital Temperature DisplayInternal LightHigh/Low Temperature AlarmMinimum/Maximum Temperature RecordingAutomatic Temperature & Fridge Operation Data RecordingDoor Open AlarmAlarm Battery Back-UpSecond Temperature ProbeOff Cycle Auto Defrost	Door Style	Solid
Key Lock✓Digital Temperature Control✓Digital Temperature Display✓Internal Light✓High/Low Temperature Alarm✓Minimum/Maximum Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Door Open Alarm✓Mains Failure Alarm✓Alarm Battery Back-Up✓Off Cycle Auto Defrost✓	Door Hinging	reversed at time of
Digital Temperature Control✓Digital Temperature Display✓Internal Light✓High/Low Temperature Alarm✓Minimum/Maximum Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Door Open Alarm✓Mains Failure Alarm✓Alarm Battery Back-Up✓Off Cycle Auto Defrost✓	Self Closing Door	\checkmark
Digital Temperature Display✓Internal Light✓High/Low Temperature Alarm✓Minimum/Maximum Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Door Open Alarm✓Mains Failure Alarm✓Alarm Battery Back-Up✓Second Temperature Probe✓Off Cycle Auto Defrost✓	Key Lock	\checkmark
Internal Light✓High/Low Temperature Alarm✓Minimum/Maximum Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Door Open Alarm✓Mains Failure Alarm✓Alarm Battery Back-Up✓Second Temperature Probe✓Off Cycle Auto Defrost✓	Digital Temperature Control	\checkmark
High/Low Temperature Alarm✓Minimum/Maximum Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Door Open Alarm✓Mains Failure Alarm✓Alarm Battery Back-Up✓Second Temperature Probe✓Off Cycle Auto Defrost✓	Digital Temperature Display	\checkmark
Minimum/Maximum Temperature RecordingAutomatic Temperature & Fridge Operation Data RecordingDoor Open AlarmMains Failure AlarmAlarm Battery Back-UpSecond Temperature ProbeOff Cycle Auto Defrost	Internal Light	\checkmark
Temperature RecordingAutomatic Temperature & Fridge Operation Data RecordingDoor Open AlarmMains Failure AlarmAlarm Battery Back-UpSecond Temperature ProbeOff Cycle Auto Defrost	High/Low Temperature Alarm	\checkmark
Operation Data RecordingDoor Open AlarmMains Failure Alarm✓Alarm Battery Back-Up✓Second Temperature Probe✓Off Cycle Auto Defrost		\checkmark
Mains Failure Alarm✓Alarm Battery Back-Up✓Second Temperature Probe✓Off Cycle Auto Defrost✓		\checkmark
Alarm Battery Back-Up√Second Temperature Probe√Off Cycle Auto Defrost√	Door Open Alarm	\checkmark
Second Temperature Probe√Off Cycle Auto Defrost√	Mains Failure Alarm	\checkmark
Off Cycle Auto Defrost 🗸 🗸	Alarm Battery Back-Up	\checkmark
	Second Temperature Probe	\checkmark
Fan Assisted Cooling 🛛 🗸	Off Cycle Auto Defrost	\checkmark
	Fan Assisted Cooling	\checkmark
Remote Alarm Contacts 🗸 🗸 🗸	Remote Alarm Contacts	\checkmark
Access Port ✓	Access Port	\checkmark
DH Green Book Guidelines Compliant		\checkmark



01256 705 570











The touch screen controller is completely flat so can be thoroughly cleaned and disinfected as there are no raised buttons to collect dirt and germs. The controller displays, alarms and records minimum and maximum temperatures for both temperature probes. Like a mobile phone touch screen it locks after 30 seconds to ensure that buttons can't be activated accidently.

For extra security, there is a digital lock version RLDF0519DIGLOCK which solves the problem of generic keys, but whatever the preferred model, for a small additional cost we can provide a manufacturers' calibration certificate from our in house UKAS temperature calibration laboratory No:8898.

We are confident that this pharmacy refrigerator will provide you with many years of fault free service. However, for extra peace of mind your RLDF0519 comes complete with a FREE UK 5 year parts and labour warranty.



While you're registering your warranty, why not purchase a micro SD card and adapter for transferring data recorded by the controller from the fridge to your computer at half price?

> The IntelliCold[®] controller records alarm states, fridge operation, door openings and temperature data for both probes at minute intervals. You can only view and store this data on a computer by purchasing a specially encoded micro SD card from Labcold. This data helps you with record keeping and regulatory inspections, plus if you have an issue, you can establish the exact duration and severity of the event.

RLDF0519 Pharmacy & Vaccine Refrigerator

Capacity (Litres)150StyleUnder CounterExterior Dimensions (HxWxD)835 x 600 x 600mm (HxWxD)Interior Dimensions (HxWxD)690 x 480 x 410mmTemperature Range+2°C to +8°COperating Temperature+5°CPower Consumption Kwh/24hrs1.41Interior ConstructionPowder Coated SteelExterior ConstructionPowder Coated SteelShelves3Net Weight (kg)51Internal Drawers Available·Door StyleSolidDoor HingingRight (can be reversed at time of manufacture)Self Closing Door·Key Lock·Digital Temperature Control·Joigtal Temperature Display·Minimum/Maximum Temperature Recording·Automatic Temperature Alarm·Door Open Alarm·Mains Failure Alarm·Alarm Battery Back-Up·Off Cycle Auto Defrost·Fan Assisted Cooling·	Part Number	RLDF0519
Exterior Dimensions (HXWxD)835 x 600 x 600mmInterior Dimensions (HXWxD)690 x 480 x 410mmTemperature Range+2°C to +8°COperating Temperature+5°CPower Consumption Kwh/24hrs1.41Interior ConstructionPowder Coated SteelExterior ConstructionPowder Coated SteelShelves3Net Weight (kg)51Internal Drawers Available✓Door StyleSolidDoor HingingSelf Closing Door✓Key Lock✓Digital Temperature Othorp✓Minimum/Maximum Temperature Recording✓Minimum/Maximum Temperature Recording✓AutomaticTemperature Alarm✓Mains Failure Alarm✓Alarm Battery Back-Up✓Off Cycle Auto Defrost✓	Capacity (Litres)	150
Interior Dimensions (HxWxD)835 x 600 x 600mmInterior Dimensions (HxWxD)690 x 480 x 410mmTemperature Range+2°C to +8°COperating Temperature+5°CPower Consumption Kwh/24hrs1.41Interior ConstructionPowder Coated SteelExterior ConstructionPowder Coated SteelShelves3Net Weight (kg)51Internal Drawers Available✓Door StyleSolidDoor HingingRight (can be reversed at time of manufacture)Self Closing Door✓Key Lock✓Digital Temperature Control✓Joigtal Temperature Display✓Hinhimum/Maximum Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Door Open Alarm✓Alarm Battery Back-Up✓Off Cycle Auto Defrost✓	Style	Under Counter
Harmonic (HxWxD)690 x 480 x 410mmTemperature Range+2°C to +8°COperating Temperature+5°CPower Consumption Kwh/24hrs1.41Interior ConstructionPowder Coated SteelExterior ConstructionPowder Coated SteelShelves3Net Weight (kg)51Internal Drawers Available·Door StyleSolidDoor HingingRight (can be reversed at time of manufacture)Self Closing Door·Key Lock·Digital Temperature Control·Joigtal Temperature Display·Internal Light·High/Low Temperature Alarm·Minimum/Maximum Temperature Recording·Door Open Alarm·Mains Failure Alarm·Alarm Battery Back-Up·Off Cycle Auto Defrost·		835 x 600 x 600mm
Operating Temperature+5°CPower Consumption Kwh/24hrs1.41Interior ConstructionPowder Coated SteelExterior ConstructionPowder Coated SteelShelves3Net Weight (kg)51Internal Drawers Available✓Door StyleSolidDoor HingingRight (can be reversed at time of manufacture)Self Closing Door✓Key Lock✓Digital Temperature Control✓Jinternal Light✓High/Low Temperature Alarm✓Minimum/Maximum Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Door Open Alarm✓Alarm Battery Back-Up✓Off Cycle Auto Defrost✓		690 x 480 x 410mm
Power Consumption Kwh/24hrs1.41Interior ConstructionPowder Coated SteelExterior ConstructionPowder Coated SteelShelves3Net Weight (kg)51Internal Drawers AvailableJoor StyleSolidDoor HingingRight (can be reversed at time of manufacture)Self Closing DoorKey LockDigital Temperature ControlJinternal LightHigh/Low Temperature AlarmMinimum/Maximum Temperature RecordingAutomatic Temperature & Fridge Operation Data RecordingJoor Open AlarmAlarm Battery Back-UpOff Cycle Auto DefrostOff Cycle Auto Defrost	Temperature Range	+2°C to +8°C
Kwh/24hrs1.41Interior ConstructionPowder Coated SteelExterior ConstructionPowder Coated SteelShelves3Net Weight (kg)51Internal Drawers Available✓Door StyleSolidDoor HingingRight (can be reversed at time of manufacture)Self Closing Door✓Key Lock✓Digital Temperature Control✓Jinternal Light✓High/Low Temperature Alarm✓Minimum/Maximum Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Mains Failure Alarm✓Alarm Battery Back-Up✓Off Cycle Auto Defrost✓	Operating Temperature	+5°C
Exterior ConstructionPowder Coated SteelShelves3Net Weight (kg)51Internal Drawers Available✓Door StyleSolidDoor HingingRight (can be reversed at time of manufacture)Self Closing Door✓Key Lock✓Digital Temperature Control✓Internal Light✓High/Low Temperature Alarm✓Minimum/Maximum Temperature Recording✓Door Open Alarm✓Mains Failure Alarm✓Alarm Battery Back-Up✓Second Temperature Probe✓Off Cycle Auto Defrost✓		1.41
Shelves3Net Weight (kg)51Internal Drawers Available✓Door StyleSolidDoor HingingRight (can be reversed at time of manufacture)Self Closing Door✓Key Lock✓Digital Temperature Control✓Digital Temperature Display✓High/Low Temperature Alarm✓Minimum/Maximum Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Door Open Alarm✓Alarm Battery Back-Up✓Off Cycle Auto Defrost✓	Interior Construction	Powder Coated Steel
Net Weight (kg)51Internal Drawers Available✓Door StyleSolidDoor HingingRight (can be reversed at time of manufacture)Self Closing Door✓Key Lock✓Digital Temperature Control✓Digital Temperature Display✓Internal Light✓High/Low Temperature Alarm✓Minimum/Maximum Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Door Open Alarm✓Alarm Battery Back-Up✓Off Cycle Auto Defrost✓	Exterior Construction	Powder Coated Steel
Internal Drawers AvailableInternal Drawers AvailableDoor StyleSolidBoor HingingRight (can be reversed at time of manufacture)Self Closing Door✓Key Lock✓Digital Temperature Control✓Digital Temperature Display✓High/Low Temperature Alarm✓Minimum/Maximum Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Door Open Alarm✓Alarm Battery Back-Up✓Off Cycle Auto Defrost✓	Shelves	3
Door StyleSolidDoor HingingRight (can be reversed at time of manufacture)Self Closing Door✓Key Lock✓Migital Temperature Control✓Jigital Temperature Display✓Internal Light✓High/Low Temperature Alarm✓Minimum/Maximum Temperature Recording✓Joor Open Alarm✓Mains Failure Alarm✓Alarm Battery Back-Up✓Off Cycle Auto Defrost✓	Net Weight (kg)	51
Door HingingRight (can be reversed at time of manufacture)Self Closing DoorSelf Closing DoorKey LockDigital Temperature ControlJoigital Temperature DisplayInternal LightHigh/Low Temperature AlarmMinimum/Maximum Temperature RecordingJoor Open AlarmMains Failure AlarmAlarm Battery Back-UpSecond Temperature ProbeOff Cycle Auto Defrost	Internal Drawers Available	\checkmark
Door Hingingreversed at time of manufacture)Self Closing DoorKey LockDigital Temperature ControlDigital Temperature DisplayInternal LightHigh/Low Temperature AlarmMinimum/Maximum Temperature RecordingAutomatic Temperature & Fridge Operation Data RecordingDoor Open AlarmAlarm Battery Back-UpSecond Temperature ProbeOff Cycle Auto Defrost	Door Style	Solid
Key Lock✓Digital Temperature Control✓Digital Temperature Display✓Internal Light✓High/Low Temperature Alarm✓Minimum/Maximum Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Door Open Alarm✓Mains Failure Alarm✓Alarm Battery Back-Up✓Off Cycle Auto Defrost✓	Door Hinging	reversed at time of
Digital Temperature Control✓Digital Temperature Display✓Internal Light✓High/Low Temperature Alarm✓Minimum/Maximum Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Door Open Alarm✓Mains Failure Alarm✓Alarm Battery Back-Up✓Off Cycle Auto Defrost✓	Self Closing Door	\checkmark
Digital Temperature Display✓Internal Light✓High/Low Temperature Alarm✓Minimum/Maximum Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Door Open Alarm✓Mains Failure Alarm✓Alarm Battery Back-Up✓Second Temperature Probe✓Off Cycle Auto Defrost✓	Key Lock	\checkmark
Internal Light✓High/Low Temperature Alarm✓Minimum/Maximum Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Door Open Alarm✓Mains Failure Alarm✓Alarm Battery Back-Up✓Second Temperature Probe✓Off Cycle Auto Defrost✓	Digital Temperature Control	\checkmark
High/Low Temperature Alarm✓Minimum/Maximum Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Door Open Alarm✓Mains Failure Alarm✓Alarm Battery Back-Up✓Second Temperature Probe✓Off Cycle Auto Defrost✓	Digital Temperature Display	\checkmark
Minimum/Maximum Temperature RecordingAutomatic Temperature & Fridge Operation Data RecordingDoor Open AlarmMains Failure AlarmAlarm Battery Back-UpSecond Temperature ProbeOff Cycle Auto Defrost	Internal Light	\checkmark
Temperature RecordingAutomatic Temperature & Fridge Operation Data RecordingDoor Open AlarmMains Failure AlarmAlarm Battery Back-UpSecond Temperature ProbeOff Cycle Auto Defrost	High/Low Temperature Alarm	\checkmark
Operation Data RecordingDoor Open AlarmMains Failure Alarm✓Alarm Battery Back-Up✓Second Temperature Probe✓Off Cycle Auto Defrost		\checkmark
Mains Failure Alarm✓Alarm Battery Back-Up✓Second Temperature Probe✓Off Cycle Auto Defrost✓		\checkmark
Alarm Battery Back-Up√Second Temperature Probe√Off Cycle Auto Defrost√	Door Open Alarm	\checkmark
Second Temperature Probe√Off Cycle Auto Defrost√	Mains Failure Alarm	\checkmark
Off Cycle Auto Defrost 🗸 🗸	Alarm Battery Back-Up	\checkmark
	Second Temperature Probe	\checkmark
Fan Assisted Cooling 🛛 🗸	Off Cycle Auto Defrost	\checkmark
	Fan Assisted Cooling	\checkmark
Remote Alarm Contacts 🗸 🗸 🗸	Remote Alarm Contacts	\checkmark
Access Port ✓	Access Port	√
DH Green Book Guidelines Compliant		\checkmark



01256 705 570











The touch screen controller is completely flat so can be thoroughly cleaned and disinfected as there are no raised buttons to collect dirt and germs. The controller displays, alarms and records minimum and maximum temperatures for both temperature probes. Like a mobile phone touch screen it locks after 30 seconds to ensure that buttons can't be activated accidently.

For extra security, there is a digital lock version RLDG1019DIGLOCK which solves the problem of generic keys, but whatever the preferred model, for a small additional cost we can provide a manufacturers' calibration certificate from our in house UKAS temperature calibration laboratory No:8898.

We are confident that this pharmacy refrigerator will provide you with many years of fault free service. However, for extra peace of mind your RLDG1019 comes complete with a FREE UK 5 year parts and labour warranty.





While you're registering your warranty, why not purchase a micro SD card and adapter for transferring data recorded by the controller from the fridge to your computer at half price?

The IntelliCold[®] controller records alarm states, fridge operation, door openings and temperature data for both probes at minute intervals. You can only view and store this data on a computer by purchasing a specially encoded micro SD card from Labcold. This data helps you with record keeping and regulatory inspections, plus if you have an issue, you can establish the exact duration and severity of the event.

RLDG1019 Pharmacy & Vaccine Refrigerator

Part Number	RLDG1019
Capacity (Litres)	340
Style	Free Standing
Exterior Dimensions (HxWxD)	1510 x 600 x 700mm
Interior Dimensions (HxWxD)	1358 x 480 x 500mm
Temperature Range	+2°C to +8°C
Operating Temperature	+5°C
Power Consumption Kwh/24hrs	1.9
Interior Construction	Powder Coated Steel
Exterior Construction	Powder Coated Steel
Shelves	б
Net Weight (kg)	91
Internal Drawers Available	\checkmark
Door Style	Glass
Door Hinging	Right (can be reversed at time of manufacture)
Self Closing Door	\checkmark
Key Lock	\checkmark
Digital Temperature Control	\checkmark
Digital Temperature Display	✓
Internal Light	\checkmark
High/Low Temperature Alarm	✓
Minimum/Maximum Temperature Recording	\checkmark
Automatic Temperature & Fridge Operation Data Recording	✓
Door Open Alarm	\checkmark
Mains Failure Alarm	\checkmark
Alarm Battery Back-Up	\checkmark
Second Temperature Probe	\checkmark
Off Cycle Auto Defrost	\checkmark
Fan Assisted Cooling	\checkmark
Remote Alarm Contacts	\checkmark
Access Port	\checkmark
DH Green Book Guidelines Compliant	✓



01256 705 570









The touch screen controller is completely flat so can be thoroughly cleaned and disinfected as there are no raised buttons to collect dirt and germs. The controller displays, alarms and records minimum and maximum temperatures for both temperature probes. Like a mobile phone touch screen it locks after 30 seconds to ensure that buttons can't be activated accidently.

For extra security, there is a digital lock version RLDG1019DIGLOCK which solves the problem of generic keys, but whatever the preferred model, for a small additional cost we can provide a manufacturers' calibration certificate from our in house UKAS temperature calibration laboratory No:8898.

We are confident that this pharmacy refrigerator will provide you with many years of fault free service. However, for extra peace of mind your RLDG1019 comes complete with a FREE UK 5 year parts and labour warranty.





While you're registering your warranty, why not purchase a micro SD card and adapter for transferring data recorded by the controller from the fridge to your computer at half price?

The IntelliCold[®] controller records alarm states, fridge operation, door openings and temperature data for both probes at minute intervals. You can only view and store this data on a computer by purchasing a specially encoded micro SD card from Labcold. This data helps you with record keeping and regulatory inspections, plus if you have an issue, you can establish the exact duration and severity of the event.

RLDG1019 Pharmacy & Vaccine Refrigerator

Part Number	RLDG1019
Capacity (Litres)	340
Style	Free Standing
Exterior Dimensions (HxWxD)	1510 x 600 x 700mm
Interior Dimensions (HxWxD)	1358 x 480 x 500mm
Temperature Range	+2°C to +8°C
Operating Temperature	+5°C
Power Consumption Kwh/24hrs	1.9
Interior Construction	Powder Coated Steel
Exterior Construction	Powder Coated Steel
Shelves	6
Net Weight (kg)	91
Internal Drawers Available	\checkmark
Door Style	Glass
Door Hinging	Right (can be reversed at time of manufacture)
Self Closing Door	\checkmark
Key Lock	\checkmark
Digital Temperature Control	\checkmark
Digital Temperature Display	\checkmark
Internal Light	✓
High/Low Temperature Alarm	✓
Minimum/Maximum Temperature Recording	\checkmark
Automatic Temperature & Fridge Operation Data Recording	✓
Door Open Alarm	\checkmark
Mains Failure Alarm	\checkmark
Alarm Battery Back-Up	\checkmark
Second Temperature Probe	\checkmark
Off Cycle Auto Defrost	\checkmark
Fan Assisted Cooling	\checkmark
Remote Alarm Contacts	\checkmark
Access Port	\checkmark
DH Green Book Guidelines Compliant	\checkmark



01256 705 570









The touch screen controller is completely flat so can be thoroughly cleaned and disinfected as there are no raised buttons to collect dirt and germs. The controller displays, alarms and records minimum and maximum temperatures for both temperature probes. Like a mobile phone touch screen it locks after 30 seconds to ensure that buttons can't be activated accidently.

For extra security, there is a digital lock version RLDF1519DIGLOCK which solves the problem of generic keys, but whatever the preferred model, for a small additional cost we can provide a manufacturers' calibration certificate from our in house UKAS temperature calibration laboratory No:8898.

We are confident that this pharmacy refrigerator will provide you with many years of fault free service. However, for extra peace of mind your RLDF1519 comes complete with a FREE UK 5 year parts and labour warranty.





01256 705 570

why not purchase a micro SD card and adapter for transferring data recorded by the controller from the fridge to your computer at half price?

> The IntelliCold[®] controller records alarm states, fridge operation, door openings and temperature data for both probes at minute intervals. You can only view and store this data on a computer by purchasing a specially encoded micro SD card from Labcold. This data helps you with record keeping and regulatory inspections, plus if you have an issue, you can establish the exact duration and severity of the event.

RLDF1519 Pharmacy & Vaccine Refrigerator

Part Number	RLDF1519
Capacity (Litres)	440
Style	Free Standing
Exterior Dimensions (HxWxD)	1875 x 600 x 700mm
Interior Dimensions (HxWxD)	1724 x 480 x 500mm
Temperature Range	+2°C to +8°C
Operating Temperature	+5℃
Power Consumption Kwh/24hrs	2.55
Interior Construction	Powder Coated Steel
Exterior Construction	Powder Coated Steel
Shelves	6
Net Weight (kg)	93
Internal Drawers Available	\checkmark
Door Style	Solid
Door Hinging	Right (can be reversed at time of manufacture)
Self Closing Door	√
Key Lock	\checkmark
Digital Temperature Control	\checkmark
Digital Temperature Display	\checkmark
Internal Light	\checkmark
High/Low Temperature Alarm	\checkmark
Minimum/Maximum Temperature Recording	✓
Automatic Temperature & Fridge Operation Data Recording	\checkmark
Door Open Alarm	\checkmark
Mains Failure Alarm	\checkmark
Alarm Battery Back-Up	\checkmark
Second Temperature Probe	\checkmark
Off Cycle Auto Defrost	\checkmark
Fan Assisted Cooling	\checkmark
Remote Alarm Contacts	\checkmark
Access Port	\checkmark
DH Green Book Guidelines Compliant	\checkmark











The touch screen controller is completely flat so can be thoroughly cleaned and disinfected as there are no raised buttons to collect dirt and germs. The controller displays, alarms and records minimum and maximum temperatures for both temperature probes. Like a mobile phone touch screen it locks after 30 seconds to ensure that buttons can't be activated accidently.

For extra security, there is a digital lock version RLDG1519DIGLOCK which solves the problem of generic keys, but whatever the preferred model, for a small additional cost we can provide a manufacturers' calibration certificate from our in house UKAS temperature calibration laboratory No:8898.

We are confident that this pharmacy refrigerator will provide you with many years of fault free service. However, for extra peace of mind your RLDG1519 comes complete with a FREE UK 5 year parts and labour warranty.





While you're registering your warranty, why not purchase a micro SD card and adapter for transferring data recorded by the controller from the fridge to your computer at half price?

The IntelliCold[®] controller records alarm states, fridge operation, door openings and temperature data for both probes at minute intervals. You can only view and store this data on a computer by purchasing a specially encoded micro SD card from Labcold. This data helps you with record keeping and regulatory inspections, plus if you have an issue, you can establish the exact duration and severity of the event.

RLDG1519 Pharmacy & Vaccine Refrigerator

Part Number	RLDG1519
Capacity (Litres)	440
Style	Free Standing
Exterior Dimensions (HxWxD)	1875 x 600 x 700mm
Interior Dimensions (HxWxD)	1724 x 480 x 500mm
Temperature Range	+2°C to +8°C
Operating Temperature	+5°C
Power Consumption Kwh/24hrs	2.64
Interior Construction	Powder Coated Steel
Exterior Construction	Powder Coated Steel
Shelves	б
Net Weight (kg)	105
Internal Drawers Available	\checkmark
Door Style	Glass
Door Hinging	Right (can be reversed at time of manufacture)
Self Closing Door	\checkmark
Key Lock	\checkmark
Digital Temperature Control	\checkmark
Digital Temperature Display	\checkmark
Internal Light	\checkmark
High/Low Temperature Alarm	√
Minimum/Maximum Temperature Recording	\checkmark
Automatic Temperature & Fridge Operation Data Recording	\checkmark
Door Open Alarm	\checkmark
Mains Failure Alarm	\checkmark
Alarm Battery Back-Up	\checkmark
Second Temperature Probe	\checkmark
Off Cycle Auto Defrost	\checkmark
Fan Assisted Cooling	\checkmark
Remote Alarm Contacts	\checkmark
Access Port	\checkmark
DH Green Book Guidelines Compliant	✓



01256 705 570









The touch screen controller is completely flat so can be thoroughly cleaned and disinfected as there are no raised buttons to collect dirt and germs. The controller displays, alarms and records minimum and maximum temperatures for both temperature probes. Like a mobile phone touch screen it locks after 30 seconds to ensure that buttons can't be activated accidently.

For extra security, there is a digital lock version RLDF0119DIGLOCK which solves the problem of generic keys, but whatever the preferred model, for a small additional cost we can provide a manufacturers' calibration certificate from our in house UKAS temperature calibration laboratory No:8898.

We are confident that this pharmacy refrigerator will provide you with many years of fault free service. However, for extra peace of mind your RLDF0119 comes complete with a FREE UK 5 year parts and labour warranty.





While you're registering your warranty, why not purchase a micro SD card and adapter for transferring data recorded by the controller from the fridge to your computer at half price?

The IntelliCold® controller records alarm states, fridge operation, door openings and temperature data for both probes at minute intervals. You can only view and store this data on a computer by purchasing a specially encoded micro SD card from Labcold. This data helps you with record keeping and regulatory inspections, plus if you have an issue, you can establish the exact duration and severity of the event.

www.labcold.com

RLDF0119 Pharmacy & Vaccine Refrigerator

Part Number	RLDF0119
Capacity (Litres)	36
Style	Bench Top
Exterior Dimensions (HxWxD)	540 x 450 x 510mm
Interior Dimensions (HxWxD)	392 x 331 x 226mm
Operating Temperature	+5°C
Temperature Range	+2°C to +8°C
Power Consumption Kwh/24hrs	1.28
Interior Construction	Moulded Plastic
Exterior Construction	Powder Coated Steel
Brackets for Wall Mounting	\checkmark
Shelves	2
Net Weight (kg)	30
Door Style	Solid
Door Hinging	Right (can be reversed at time of manufacture)
Self Closing Door	\checkmark
Key Lock	\checkmark
Digital Temperature Display	\checkmark
Internal Light	\checkmark
High/Low Temperature Alarm	\checkmark
Minimum/Maximum Temperature Recording	\checkmark
Automatic Temperature & Fridge Operation Data Recording	✓
Door Open Alarm	\checkmark
Mains Failure Alarm	\checkmark
Alarm Battery Back-Up	\checkmark
Second Temperature Probe	\checkmark
Off Cycle Auto Defrost	\checkmark
Fan Assisted Cooling	\checkmark
Remote Alarm Contacts	\checkmark
Access Port	\checkmark
DH Green Book Guidelines Compliant	\checkmark



01256 705 570