











UPDATED: 12/02/2019

DG-BluePro™-Diamond Extra

Nitrile powder free disposable gloves

A 29cm long, extra thick nitrile semi-disposable with added diamond pattern on the front and the back of the glove. 6mil thickness is twice as thick as a normal disposable glove offering superior chemical and mechanical protection. Diamond textured pattern creates a suction style grip for excellent grip in dry, wet or oily applications. Can be used in lieu of a standard latex washing up style to remove the risk of latex allergies. Packed in boxes of 50 hands, extremely cost effective.



FEATURES AND TECHNOLOGY











SUPERIOR GRIP





RAISED DIAMOND PATTERN



NITRILE DISPOSABLE

TYPICAL INDUSTRIES











AGRICULTURE



FOOD PROCESSING



JANITORIAL

TECHNICAL INFORMATION

ADDED DEF #		
ORDER REF#	G/DGBLUEPRO-DE	
COATING MATERIAL	N/A	
PACKING	PER PACK: 1	PER CASE: 10
SIZES AVAILABLE	M,L,XL,2XL	
EU TYPE CERTIFICATION BY	SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, UK (Notified Body No. 0321)	

CERTIFICATION AND STANDARDS (SEE OVERLEAF FOR FURTHER DETAILS)



'X' denotes not tested.
'Where applicable, EN388:2016 scores take precedent and are ongoing.
'There is no correlation between coupe test levels and EN ISO 13997 / TDM cut test levels.



VIRUS


Protection against viruses - PASS

0086









Fax: +44 (0)1902 451 271







Registered in England No. 2035621













UPDATED: 12/02/2019

CERTIFICATION LEGENDS



* For dulling during cut resistance test (6.2), the coupe test results are only indicative while the TDM cut resistance test (6.3) is the reference performance result.

FN ISO 374-1 :2016 / TYPE



С

D

Methanol

Acetone

Toluene

Acetonitrile

Dichloromethane

Carbon Disulphide

Diethylamine

Ethyl Acetate

Tetrahvdrofuran

FNISO

374-5:2016

greater against six of the chemicals listed in EN ISO 374-1 (below). The tested chemicals are identified by their code letters under the flask pictogram. **TYPE B** - Achieved level 2 or greater against at least **three** of the chemicals TYPE C - Achieved at least a level 1 against one of the chemicals.

n-Heptane Sodium Hydroxide (40%) Sulphuric Acid (96%) М Nitric Acid (65%) Ammonium Hydroxide (25%) 0 Hydrogen Peroxide (30%) Hydrogen Peroxide (30%) S Hydrofluoric Acid (40%) Formaldehyde (37%)

TYPE A - Gloves have achieved level 2 or

EN407:2004

пппппп

EN511:2006

For details regarding maximum permissable user exposure, see seperate sheet.

FURTHER INFORMATION

STORAGE / TRANSPORT: Keep away from direct sunlight; store in a cool dry place. Keep away from ozone sources or naked flame. Store the gloves in their original packaging. During transportation, ensure the product is well packaged and protected in order to prevent any damage.


PRECAUTIONS BEFORE USE: 1. Gloves should not be used when there is a risk of entanglement with moving machine parts. 2. Before usage and periodically during usage, inspect the gloves for any defects or imperfections. Avoid wearing damaged, dirty or worn out gloves. 3. The gloves should not come in contact with a naked flame or fire. 4. Do not subject to high speed or serrated blades. 5. Always read enclosed user instructions before using these gloves. 6. When used, protective gloves may provide less resistance to the dangerous chemicals due to changes in physical properties. 7. Movements, snagging, rubbing, de-gradation caused by the chemical contact etc. may reduce the actual use time significantly. For corrosive chemicals, degradation can be the most important factor to consider in selection of chemical resistant gloves.

CONSTITUENTS / ALLERGIES: Some gloves may contain ingredients which are known to be a possible cause of allergies in sensitive persons who may develop irritant and/or allergic contact reactions. If an allergic reaction should occur seek medical advice immediately. This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

For more information about this product, or to access the Declaration of Conformity or Product Certification, visit; https://www.ultimateindustrial.co.uk/product/1109-DG-BluePro-Diamond-Extra

If appropriate to the product, EC/EU Declaration of Conformities, relevant certification and supporting documentation are available to access through your distributor, at the above web address(s) or by contacting UCi customer services quoting the product reference code. This document and any other statement provided herein by or on behalf of UCi are given for informational purposes and do not constitute a contractual agreement nor warranty of merchantability. UCi assumes no responsibility for the suitability or adequacy of an end user's selection of product for a specific purpose. The manufacturer reserves the right to make any modifications it deems necessary. All product and company names are trademarks of their respective holders. © UCi Limited, 2019











Registered in England No. 2035621

¹Testing carried out on the palm material. Except in cases where the glove is equal to or over 400mm - where the cuff is tested also tested. ² 'X' denotes Not Tested. ³ Where applicable, EN388:2016 scores take precedent and are ongoing. There is no correlation between coupe test levels and ISO 13997 /TDM cut test levels. Where both EN388:2016 and EN388:2003 scores are shown, the latter is shown for informational purposes only.