

# TECHNICAL SPECIFICATION

RESPIRATORY PROTECTION



## Flexinet® Mask FFP3 Valved (832)

Product Code: BER130-001-M00 / BER130-001-L1X



### Description

The Flexinet™ disposable mask has an ergonomic 3D design to fit most face shapes, with extremely low breathing resistance and mesh outer shell to help the mask retain its shape.

- High efficiency (99% minimum) filtering

### Options

Box of 5 code: BER130-001-M00

Retail pack x 1 : BER130-001-L1X



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.  
Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com  
Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com.  
Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.  
Page 1 of 3 / Issued 04 Feb 2021 / Copyright 2018 - 2020. JSP Limited. All Rights Reserved.



[www.jspsafety.com](http://www.jspsafety.com)

[sales@jspsafety.com](mailto:sales@jspsafety.com)

UK tel: +44 (0)1993 826050

## FEATURES



**Comfort**  
A 360° comfort foam area around the inside of the mask provides a perfect fit



**Protective Grill**  
Flexible cover to protect and retain the shape of the mask and protect the wearer against possible damage to the filter



**Advanced Valve**  
Advanced design valve allows for lower breathing resistance

## COMPATIBLE PRODUCTS

EVO® Gas Goggle  
EVO® Goggle Double Lens  
EVO® Goggle Single Lens  
Sonis® Compact Ear Defenders  
Sonis®1 Ear Defenders  
Sonis®2 Ear Defenders  
Sonis®3 Ear Defenders  
Stealth™ 16G  
Stealth™ 7000  
Stealth™ 8000  
Stealth™ 9000  
Stealth™ Coverlite™ Overspec  
Thermex™ Double Lens Goggle

## ACCESSORIES

Portacount/AccuFIT Quantitative/Qualitative Face Fit Testing Kit & Spares

## SAFETY STANDARDS

EN 149:2001 + A1:2009

## CERTIFICATION

CE 682743 issued by BSI

## SPECIFICATIONS

Classification

FFP3 (Filtering Facepiece Particulate, Valved)

Filter Type

P (Protects Against Solid and Liquid Aerosols)

Usage

NR (Non-Reusable)

**D** (D) Resistance to dust clogging  
**Yes - D marking = passes optional clogging test**

 Activated Carbon Layer

**No**

Minimum Filtration Efficiency

 **99% For FFP3 Rated**

Maximum Total Inward Leakage (TIL)

**2%**

Nominal Protection Factor (NPF)

**50**

UK Assigned Protection Factor (APF)

**20**

Mask Design

**Mesh Outer Shell**

 Exhalation Valve

**Advanced Valve**

 4 Point Harness adjustment system

**Yes**

 Nose Bridge

**Moulded in mask**

Latex Free

**No**

Metal Free

**Yes**

Mask Material

**Polypropylene**

Filter Shelf Life

**5 Years**

 BSI Kitemark

**Yes**

 Product Weight

**26g (Approx)**

## APPLICATIONS

- Mining, Aggregates and Quarrying
- Agriculture
- Forestry & Landscaping
- Manufacturing
- Constuction & Infrastructure
- Scaffolding & Roofing
- Welding (mild)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.  
Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com  
Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com.  
Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.  
Page 2 of 3 / Issued 04 Feb 2021 / Copyright 2018 - 2020, JSP Limited. All Rights Reserved.



## INSTRUCTIONS FOR USE

- Mask must be fitted in accordance with the instructions supplied
- Care must be taken to ensure that the correct mask type is selected for the work to be carried out
- If in doubt as to the type of mask required, seek professional guidance

## LIMITATIONS OF USE

- Protection will only be offered if the mask is fitted correctly
- The mask, when in contact with the skin may cause allergic
- Do not use where exposure to chemical gases may be experienced
- Use in well ventilated areas only, which are not deficient in oxygen and do not contain explosive atmospheres
- Ensure good seal around the face is created before entering the hazard area
- The working life of the mask is nominally one day (this is based on a working day shift of 8 hours), however it may be affected by many factors, including work rate, airflow and concentration of any contaminant in the atmosphere. The mask should be changed immediately if,
  - a.) Breathing difficulties due to clogging are experienced,
  - b.) Breakthrough of a contaminant is detected by smell, taste or any other means, or
  - c.) The mask becomes damaged



JSP Limited. Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.  
Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jgpsafety.com](mailto:sales@jgpsafety.com) / Web: [www.jgpsafety.com](http://www.jgpsafety.com)  
Do Not Publish without written permission from JSP Limited. Contact [copyright@jgpsafety.com](mailto:copyright@jgpsafety.com).  
Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.  
Page 3 of 3 / Issued 04 Feb 2021 / Copyright 2018 - 2020, JSP Limited. All Rights Reserved.

