

TG6240

Conforming to cut level E under the new EN388:2016 standard, TG6240 has unrivalled levels of dexterity and comfort and is designed to last for long periods of time.

The MicroDex Ultra coating and new Life Extending Technology makes the TG6240 perfect for high cut risk tasks in wet, dry and oily conditions. Also features a thumb crotch to further extend the wear life of the glove.

The LXT range is certified as carbon neutral. This means that at no extra cost, your LXT glove has zero negative impact on the environment, to the point of delivery.

Ideal for

- Automotive
- Construction and utility
- Engineering and manufacturing
- Oil and gas
- Rail
- Mechanical and electrical
- Waste, recycling and local authority



KEY

- Dry
- Wet
- Heat
- Oily
- Cold
- Chemical



EN 388	4X44E
Sizes	6-11
Liner	Polyester/Glass HPPE/Steel/ Nylon/Elastane
Gauge	15gg
Coating	MicroDex Ultra
Conditions	

EN 388:2016 4 X 4 4 E	ASTM ANSI CUT LEVEL A5	EN 407:2020 X 1 X X X X
-------------------------------------	-------------------------------------	---------------------------------------

Qty/band	10 pairs
Qty/carton	100 pairs



Net zero carbon footprint

Plastic free packaging

Conforms to EN 407:2020

Resistance to oil & water

Reduction in cost in usage

Comfort & durability

Washable to 40°C
Certified up to 3 washes

Reduction in waste & landfill