



## Fatigue-Step

Fatigue relief for large, wet and oily shop floors



- Tiles link together to provide an anti-fatigue surface for particularly wet or oily areas.
- Soft, yet resilient rubber floor tiles.
- Open holes allow efficient drainage of spilt liquids.
- Effective anti-fatigue properties for prolonged standing.
- Main tiles available in two options: Standard or Nitrile
- Nitrile option has excellent resistance to oils, chemicals and grease.
- Slip tested to DIN 51130.
- Optional ramped edging in yellow or black.



## Parts

Part Number	Size	Colour	Weight (kg)
SS010001	0.9 m x 0.9 m	Black	9.95
SS020001	0.9 m x 0.9 m	Blue	10.00 kg
SS010007	0.9 m x 0.9 m	Nitrile	10

## Technical Specifications

<b>Material</b>	Rubber mix, including >50% recycled material
<b>Surface Finish</b>	Textured with holes to allow drainage
<b>Product Height</b>	18 mm
<b>Hole Size</b>	22 mm
<b>Min. Operating</b>	-20°C

<b>Temperature</b>	
<b>Max. Operating Temperature</b>	+130°C
<b>Resistance to Chemicals</b>	Natural rubber offers limited resistance to chemicals and oils
<b>Environmental Resistance</b>	Suitable for wet and dry environments. Will withstand welding splatter and spillages of other hot materials.
<b>UV Resistance</b>	Yes
<b>Typical Applications</b>	All industrial environments, Bars, Catering environments, Areas where swarf is prevalent. Children's play areas.
<b>Installation Method</b>	Loose lay interlocking tiles
<b>Accessories</b>	Bevelled corner edges
<b>Cleaning Method</b>	Wash with cold water, use vacuum cleaner or use pressure pump to remove dirt
<b>COO (Country of Origin)</b>	IN
<b>Storage and application</b>	Store at room temperature, free from deformations.
<b>Tensile Strength</b>	3 to 3.5 MPa
<b>Notes</b>	Silicone is used in the production process of the mats and a residue will possibly be left on the mat
<b>Slip Tested to</b>	DIN 51130 - R10

## Additional Information



Installation Guide



Fatigue Step DIN 51130 Ramp Slip Test

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email [sales@cobaeurope.com](mailto:sales@cobaeurope.com)

[www.cobaeurope.com](http://www.cobaeurope.com)