

ULTRANE 527





PATENT PENDING

CAT 2

F

EN388



DEXTERITY

EN407

EN 420: 5/5



Detachable fingers to limit the risk of entanglement by a rotating tool - MAPA Patent Pending Comfort, suppleness and high dexterity without any compromise on breathability and durability

SPECIFIC ADVANTAGES



) Protection against risk of entanglement

• Detachable fingers to avoid hand risk - Patent Pending

Comfort

• High suppleness and flexibility dexterity at fingertips proven breathability

Durability

• Extended use guaranteed by our exclusive process RESICOMFORT. Proven breathability, flexibility and durability of the coating.

Skin protection

- Free of harmful substances: STANDARD 100 by OEKO-TEX®, DMF Free
- Dermatologically approved

😧 Guaranteed quality

 Silicone free to prevent traces, defects on metal sheet and glass prior to painting

) Washability

• Washable 1 time at 40°C without any alteration on performances*.

INDUSTRIES

- Automotive/mechanical industry
- Mechanical industry
- Aeronautics industry
- Manufacturing
- Industrial maintenance

APPLICATIONS

- Assembly of small parts
- Automotive assembly
- Fitting small screws and fasteners
- Mechanical maintenance

Edit 27/09/2022

MAPA SAS capital de 35.000.010 € 420, rue d'Estienne d'Orves 92705 Colombes Cedex France RCS Nanterre 314 307 720



mapa-pro.com



ULTRANE 527

EN388	MECHANICAL HAZARDS	
Y	PERFORMANCE LEVELS (X = NOT TESTED)	
3 1 X	1 A	
0-4 0-5 0-4	1 A 0-4 A-F P Impact protection (optional)	
	Cut resistance according to ISO 13997	
Puncture resistance Tear resistance Blade cut resistance Abrasion resistance		
EN407	THERMAL RISKS (HEAT AND FIRE)	
	PERFORMANCE LEVELS (X = NOT TESTED)	
X 1 X	x x x	
0-4 0-4 0-4	X X X 0-4 0-4 0-4 Resistance to large quantities of molten metal	
	Small splashes of molten metal	
	Radiant heat resistant prvective heat resistance heat resistance spread	

PRODUCT DETAILS

Interior finish	Seamless textile support
Gauge	15
Exterior finish	Ventilated back
Material	Nitrile foam sandy
Cuff characteristic	Knitted Cuff
Colour.s	Black Grey
Size	6 7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	27000000000 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	8.2E+11 Ω

LOGISTIC DETAILS

Packaging

1 pair/bag 12 pairs/bag 96 pairs/carton

LEGISLATION

- $\,$ This product is not classified hazardous according to the regulation (EC) $\,$ n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/12/20/3017
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE

Edit 27/09/2022

MAPA SAS capital de 35.000.010 € 420, rue d'Estienne d'Orves 92705 Colombes Cedex France RCS Nanterre 314 307 720 * Tests carried out on unworn gloves (i.e. in new condition) which differs from the reality in the field.

