

ANTI-STATIC, SINGLE- USE GLOVE, 100% NITRILE, POWDER- FREE, SILICONE-FREE, 300MM LONG, 0.16MM THICK

Premium performance, powder-free, extended cuff, nitrile, single-use glove with anti-static properties (ESD). Extremely strong and high resistance to chemicals.

FEATURES

- › High-quality nitrile, soft and durable
- › Palm thickness 0.16mm (6 mil), weight: 9.1g, size M
- › High resistance to penetration and projections of many chemicals
- › Extended cuff (300mm length) to protect the forearm
- › Textured finish on fingertips to enhance grip
- › Powder-free, latex-free, non-sterile, AQL 1.5
- › Double Chlorinated inside and outside to offer increased comfort, low tack and reduce friction when donning
- › Anti-static properties according to EN 16350:2014: vertical resistance $14.5 \times 10^6 \Omega$
- › Eliminates static charge build-up to help prevent sparks and flare-ups in flammable environment
- › Silicone-free



SUITABLE FOR

Typical Industries

- Chemicals
- Electronics
- Manufacturing
- Oil and Gas
- Pharmaceutical
- Repair and Finishing

Suitable Applications

- Chemical Handling
- Handling Oily Components
- Laboratory Analysis
- Light Assembly
- Paint Spraying

CERTIFICATION

CAT III	EN ISO 374-1:2016/Type B	EN ISO 374-5:2016	EN 16350:2014
0598	JKPT		

See overleaf for explanation

PRODUCT INFORMATION

MATERIALS	LINER:	Nitrile
	COATING:	N/A
COLOUR	Black	
LENGTH (mm)	300 mm	
CUFF STYLE	Beaded	

ORDERING DETAILS

SIZE	CODE	PACKAGING
6/XS	SKG00630BB	100 singles per box
7/S	SKG00630BD	
8/M	SKG00630BF	10 boxes per case
9/L	SKG00630BH	
10/XL	SKG00630BJ	
11/XXL	SKG00630BL	

RECOMMENDATIONS FOR USE

- **USE:** Single use glove. Not suitable for Mechanical, thermal, heat, electrical, heavy chemical protection. Do not use near moving machines if there is a risk of entanglement.
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight.
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use.

CERTIFICATION LEGENDS



RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016

CODE	CHEMICAL	CODE	CHEMICAL	TYPE OF GLOVES	BREAKTHROUGH TIME
A	Methanol	J	n-Heptane	A	≥30 min for at least 6 chemicals
B	Acetone	K	Sodium hydroxide 40%		
C	Acetonitrile	L	Sulphuric acid 96%	B	≥30 min for at least 3 chemicals
D	Dichloromethane	M	65% Nitric acid		
E	Carbon Disulfide	N	99% Acetic acid	C	≥10 min for at least 1 chemical
F	Toluene	O	25% Ammonium hydroxide		
G	Diethylamine	P	30% Hydrogen peroxide		
H	Tetrahydrofurane	S	40% Hydrofluoric acid		
I	Ethyl acetate	T	37% Formaldehyde		



EN16350:2014 ELECTROSTATIC PROPERTIES



PROTECTION AGAINST MICRO-ORGANISMS EN 374-5

VIRUS = Glove has passed ISO 16604:2004 (method B)

EUROPE

www.globusgroup.com

E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963

