



BLACK, SINGLE-USE GLOVE, 100% NITRILE, POWDER- FREE, 240MM LONG, 0.11MM THICK

High performance, powder-free, black, nitrile, single-use examination glove. Significantly stronger alternative to latex, dual certified (Industrial and Medical) and food safe.

FEATURES

- > High-quality nitrile, soft and durable
- > Palm thickness 0.11mm (4.3 mil), weight: 5.5q, size M
- High resistance to penetration and projections of many chemicals
- Textured finish on fingertips for improved grip and touch
- > Powder-free, latex-free, non-sterile, AQL 1.5
- Chlorinated inside to offer increased comfort and reduce friction when donning
- Anti-static properties due to inherent anti-static properties of nitrile
- Approved for food handling
- > Dual labelling: PPE and medical
- Medical device compliant (MDD 93/42/EEC), conforms to EN455 (all parts)
- Tested against chemotherapy drugs according to ASTM D6978-05



SUITABLE FOR


Typical Industries

- Aerospace
- Chemical
- Electronics
- Food
- Pharmaceutical
- Manufacturing
- Oil and Gas


Suitable Applications

- Chemical Handling
- Food Handling
- Handling Oily Components
- Laboratory Analysis
- Light Assembly
- Paint Spraying
- Examination

CERTIFICATION









PRODUCT INFORMATION

MATERIALS	LINER:	Nitrile
	COATING:	N\A
COLOUR	Black	
LENGTH (mm)	240	
CUFF STYLE	Beaded	

ORDERING DETAILS

SIZE	CODE	PACKAGING
6/XS 7/S 8/M 9/L 10/XL 11/XXL	SKG00524BB SKG00524BD SKG00524BF SKG00524BH SKG00524BJ SKG00524BL	100 singles per box 10 boxes per case

RECOMMENDATIONS FOR USE

- USE: Single use glove. Not suitable for mechanical, thermal, heat, electrical, heavy chemical protection. Do not use near moving machines if there is a risk of entanglement.
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight.
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use.

CERTIFICATION LEGENDS



RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016

CODE	CHEMICAL	CODE	CHEMICAL
A	Methanol	J	n-Heptane
В	Acetone	K	Sodium hydroxide 40%
C	Acetonitrile	L	Sulphuric acid 96%
D	Dichloromethane	M	65% Nitric acid
E	Carbon Disulfide	N	99% Acetic acid
F	Toluene	0	25% Ammonium hydroxide
G	Diethylamine	P	30% Hydrogen peroxide
Н	Tetrahydrofurane	S	40% Hydrofluoric acid
I	Ethyl acetate	T	37% Formaldehyde

TYPE OF GLOVES	BREAKTHROUGH TIME
А	≥30 min for at least 6 chemicals
В	≥30 min for at least 3 chemicals
С	≥10 min for at least 1 chemical



FOOD CONTACT DIRECTIVE EC 10/2011

EN455-1:	Freedom from holes
EN455-2:	Physical properties
EN455-3:	Biological evaluation
EN455-4:	Shelf Life



PROTECTION AGAINST MICRO-ORGANISMS EN 374-5

VIRUS = Glove has passed ISO 16604: 2004 (method B)

EUROPE

www.globusgroup.com

E: sales@globus.co.uk +44 (0)161 877 4747 +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com +971 4 882 9962 F: +971 4 882 9963



Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

©2022 Globus (Shetland) Ltd | SKY-DATA-TX524-0322_1